
Solar Powered Signal Lights

Totally Self-Contained / Sealed Construction

Domed Top


- Birds stay off
- Collects sun from all angles

Polycarbonate Sealed Shell / Encasement

- Very strong
- High impact resistant
- UV stabilized
- Clear lens
- Water tight

Mounting Holes / Base

- 1/4" max. fastener size
- Use tamper-proof or regular hardware
- 7/16"-9/16" thick base for strength



Solar Panel

- Encased in shell
- High efficiency


State-of-the-Art Components

- Colored, high-intensity LEDs (no bulbs)
- Efficient solid-state circuitry

Lead Acid Battery Technology

(Sealed & encased inside)

- Longer life – up to 8 years
- High power density
- Stable voltage
- Widest operating range (-40° to 110°F)
- High pressure safety vent
- Up to 3 weeks backup storage



MODEL 501 ITEM NO. 15-73501

Range: One Mile


Colors: Amber, Red, Green, White, or Blue

Flash Rate: Steady, 10, 15, or 60 flashes/minute

Peak Intensity: 1.3 Candela

Mounting Holes: Two

Weight: 1½ lbs.



MODEL 601 ITEM NO. 15-73601

Range: Two Miles

Colors: Amber, Red, Green, or White

Flash Rate: Steady, 10, 15, or 60 flashes/minute

Peak Intensity: 3.4 Candela

Mounting Holes: Three – located on 6" diameter and 120 degrees apart

Weight: 4 lbs.



HENDERSON MARINE SUPPLY, INC.

800-523-1586 www.hendersonmarine.com

Specifications subject to change without notice. Not responsible for rust.

Page 12-11
Last Updated: 3/21/2003 12:16:00 PM